

31 years quality keep consistent

Specification

Customer name: Good Solutions Sweden AB

Manufacturer model: SCT036TSL-

Product name: Split core current transformer

Customer No.:

Characteristics:

1. Mounting type: suspended

2. Material of core: Silicon steel sheet

3. Operating temperature:-25 $^{\circ}\text{C} \sim$ +60 $^{\circ}\text{C}$


4. Storage temperature:-30 $^{\circ}$ C \sim +90 $^{\circ}$ C


5. Dielectric strength: 3500V AC/min 5mA(secondary/shell)


Outline size: (in:mm±0.5)




Product picture: (printing for reference only, subject to the actual)










Side view

Connection diagram



Φ3.5mm 3PAudio connector

Basic technical parameter table:

Approvaled by:

Input current	Output voltage	Accuracy	Work frequency	Weight
300A AC	1V AC	1%	50Hz-60Hz	310g

Noted: 2×0.2mm² Two core shielding wire,100cm-105cm in length. With 3.5mm audio plug.

Voltage output type secondary does not allow short circuit.

The above parameters are all typical values, and the actual value is subject to the actual measurement of the product. When user confirmed the parameters please sign it, the specification will be executed as an appendix of contract.

Customer sign: David Lyckslid

Web:www.poweruc.pl Date: November 29, 2023